

IP KVM Matrix Extender

Model No. **KFH151S**



Description

- The KFH151S IP KVM matrix extenders are highly optimized KVM extenders. The point-to-point connection supports transmission distance of 120m, and resolution up to 3840x2160@30Hz.
- This series of extenders can be connected to an 1G network switch to form a matrix switching system, which supports point-to-point (P2P) mode and matrix mode.
- The video compression algorithm of KFH151S matrix extender is a perfect combination of high-quality image and low latency (<16ms). The USB and video signals are transmitted through CAT5e/6/7 network cable.
- It supports USB devices such as touch screen, USB sound card, printer, etc., it can also support USB storage devices.

Features

- HDMI / USB2.0/Audio/Rs232 - IP KVM Matrix Extender
- Single and Dual screen version
- Point-to-point connection supports maximum extension distance 120m/394ft
- Can be connected to a standard network switch to form a matrix switching system
- Support seamless switching
- Support resolution up to 3840x2160@30Hz
- USB transmission rate up to 12MB/s
- HDMI lossless real-time full HD transmission
- Support local (TX) HDMI interface loop-out
- Support transmission through fiber optic and network (CAT5e/6/7)
- Support one Administrator account and one User account
- Freeze the last image after the disconnection of transmitter and receiver

Specification

Specification		KFH151S-TX	KFH151S-RX
Interfaces	HDMI Input	1	N/A
	HDMI Output	1	1
	Power	12V	12V
	LAN Port	RJ45 x 1	RJ45 x 1
	Fiber Optic Module	SFP+ x 1	SFP+ x 1
	Microphone	3.5MM Stereo Jack(Green)	3.5MM Stereo Jack(Pink)
	Speaker	3.5MM Stereo Jack(Pink)	3.5MM Stereo Jack(Green)
	Square USB	1	N/A
	USB	N/A	4
Max Resolution		3840*2160@30Hz	
Connected Cables		CAT5e/6/7 or Fiber(Depends on the fiber optic module)	
Power Input		DC12V / 3A	DC12V / 3A
Power Consumption		6W	6W
Operating Temperature		0—50 °C	
Storage Temperature		-20—60 °C	
Humidity		0—80% RH, non-condensing	
Material		Metal	
Net Weight(kg)		0.7 kg	0.7 kg
Product Dimension (W × D × H)		180mm x 209mm x 44mm	
Package Dimension (W × D × H)		243mm x 209mm x 98mm	

Connection Diagram

